



Sales Director: Darcy  
Whatsapp: 008613425174299  
Email: Darcy@szledworld.com

# Poster Led billboard



## Features:

- Cabinets can be customized to different dimension ;
- Light weight, aluminum frame and tempered glass  
Ensure graceful appearance of the player ;
- Extraordinary visual effect ;
- Adopting LED as the display element with high  
Refresh rate, high brightness ;
- Easy to install ;
- With magnets for front service .



Poster led display



Poster led display with pedestal



Beautiful



Save energy



Good ventilation



50,000 H

Life time



Ultra-light

## Application:

airport    market    grogshop    high-speed rail station    Offices    4S shop  
 Shopping Guide    convention center    bank

## Technical Specifications:

Items	P2.5mm	P3mm	P4mm	P5mm	P6mm
Pixel	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B
Configuration	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1	SMD 3-in-1
Pixel Pitch	2.5mm	3mm	4mm	5mm	6mm
Pixel Density	160,000	111,111	62,500	40,000	27,777
Module Size(mm)	160x160	192x192or 192x96	256x128	160x160or 320x160	192x192 or 384x192
Pixels/Module	64x64	64x64or 64x32	64x32	32x32or 64x32	32x32or 64x32
Cabinet Size(mm)	Customized				
Pixels/Cabinet	384x384	320x320	256x256	192x192	160x160
Cabinet Weight	Customized				
Brightness	1300cd/m <sup>2</sup>	1300cd/m <sup>2</sup>	1300cd/m <sup>2</sup>	1300cd/m <sup>2</sup>	1300cd/m <sup>2</sup>
Viewing Distance	>2.5m	>3m	>4m	>5m	>6m
Power Consumption	Max: 800	Max: 800	Max: 650	Max: 400	Max: 400
(W/m <sup>2</sup> )	Ave: 240	Ave: 240	Ave: 195	Ave: 120	Ave: 120
Driver Mode	1/32 scan	1/16 scan	1/16 scan	1/16 scan	1/16 scan
Cabinet Material	Cold Rolled Steel				
Refresh Rate	300-3000HZ adjustable				
LED Life	100,000 hours				
Supply Voltage	AC220V/50HZ; AC110V/60HZ				
Operating Temperature	-20°C ~ +40°C				
Operating Humidity	10% - 90%				
Viewing Angle	H: 120°; V: 120°				
Gray Scale	Red, Green and Blue each 16K				
Display Color	4096 Billion				
IP Rating	IP20				
Display Capability	Text, Graph and Video				

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to Led World.